

SEMI-RIGID ROLLED EDGE STEEL GUIDE POSTS AND UTILITY MARKER POSTS

Product code: RE135D1, RE135D2, REMP135 series

DIMENSIONS AND SPECIFICATIONS

Overall Width (facing traffic)	103mm
Delineator Face Width	90mm
Depth of Profile	25mm
Total Length	1350mm
Recommended exposed length above ground	1000mm
Material Thickness	1.5mm steel coil. Overall material thickness including coating 1.6mm
Shape	"C" channel

DEFINITION

Delnorth Rolled Safety Edge Semi-Rigid Steel Guide Posts and Marker Posts comply with AS1742.2-1994. The Delnorth Rolled Edge Post is made from 1.5mm high tensile G450 steel to AS1397. Typical Yield strength: 450-520MPa. Zinc coating Z275 minimum. All manufacturing is in accordance with AS1906.

WEATHER RESISTANCE

Delnorth Steel Posts are powder coated with the highest grade polyester powder to provide exceptional UV resistance and superior weathering characteristics. Delnorth Steel Posts comply with the following standards:

- Impact Resistance (ASTM D-2794)
- Adhesion (ISO2815)
- 2000hr Salt Spray (ASTM-117)

DURABILITY

Delnorth Rolled Edge Semi-Rigid Steel Guide Posts and Marker Posts are capable of retaining a minimum of 85% of their colour, appearance and physical properties for five years. They also retain 75% of their colour,

appearance and physical properties for at least eight years when exposed to extreme Australian weather conditions. They are fire resistant and the powder coating can withstand temperatures of up to 140 C.

PHYSICAL PROPERTIES

For bending properties refer to TUNRA Newcastle University test reports. Delnorth Steel Posts stand verticle when installed and will not deflect when subjected to wind speeds of 33m/sec. They will remain in one piece for at least 20 restraightening's.

FINISH & COLOUR

All surfaces of the Delnorth Steel posts are a smooth gloss powder coat finish to a minimum thickness of 100 microns and generally require no maintenance.

DELINEATORS

Delnorth Steel Posts can be fitted with all available types of guide post delineators and marker post stickers complying with AS1906.1.

The posts can be driven in with delineators or stickers attached.

PACKAGING

Boxes of 10 units
25 boxes per pallet
250 units per pallet
End caps included with each pallet