

DURA-POST® TUBULAR STEEL ‘FLOODWAY’ GUIDEPOSTS

Product Codes: FSG2159, FSG2160, FSG2161, FSG2162 Series

DIMENSIONS AND SPECIFICATIONS

WIDTH	Top section 600mm = 80mm wide
LENGTH	1000mm, 1200mm, 1600mm Other sizes available upon request.
INSTALLATION METHODS	1. Ground socket such as Ozpost. 2. Concrete in. 3. Surface Mount Plate (SMP) FSG2162
EXPOSED LENGTH ABOVE GROUND (RECOMMENDED)	1000-1200mm
PROFILE SHAPE	61mm DIA. at base.

DESCRIPTION

The Dura-Post floodway Guidepost is classified as a Rigid REGP. Standard lengths are 1000mm, 1200mm and 1600mm white powder coated. There is a product identification sticker denoting the installation depth mark and date of manufacture. A flattened pressed section at the top of the post houses the delineation. Dura-post Tubular Steel Floodway Guideposts are used in areas where flood waters can or do cross the road or through cuttings where ground sockets are installed.

CONSTRUCTION

The Dura-Post steel ‘floodway’ guidepost is used extensively through Australia and is manufactured according to MRTS14 Road Furniture Drawing No. 1356. Dura-Post Tubular Steel Guideposts are manufactured from C250 Pipe 50nb Extra Light (2.3mm wall thickness) and are compliant with AS1163 Coating requirements.

The posts are pressed to provide a flattened top section of 250mm in length x 80mm in width. The posts are supplied with 50mm x 200mm Class 1A reflective delineation fitted 50mm from the top of the post and comply with MRTS14 bending requirements.

COLOUR & FINISH

Hot dipped galvanised and powder coated using high grade powder with a minimum thickness of 75 microns. The standard colour is white. Other colours are available on request.

FLAMMIBILITY

This material does not support combustion.

DELINEATION

Class 1A 50mm x 200mm reflective delineation meeting AS/NZS 1906.2 specifications are fitted to both front and rear of the guideposts when supplied.

INSTALLATION METHODS

Dura-Post Tubular Steel Guideposts can be installed by either:

- Insert into ground socket or Oz-Post.
- Surface Mount Adapter (FSG2162).
- Concrete into place.

WARRANTY

Roadside Products Pty Ltd offer a 10 year manufacturer’s limited warranty for the Durapost Tubular Rigid Steel “Floodway” Guidepost system.

TERMS

This information and our technical advice, whether verbal, in writing or by way of trials, are given in good faith but without warranty. This also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided, especially that contained in our safety data and technical information sheets, and to test our products as to their suitability for the intended processes and uses.

The application use and processing of our products and the products used by you based on our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.