

IMPACT RECOVERY **SYSTEMS**

Flexible bollards, signposts and frames

Delnorth offer a highly durable range of passively safe self recovering flexible signposts, frames and bollards. When hit by vehicles, these products flex to absorb the impact then recover to their original position, even after repeated impacts.





RPS RETRO POST®



- Made from high grade rubber compound with reinforced steel cables for superior durability.
- Perfect for high-impact traffic zones, Retro Post® is selfreturning, flexible, and available in multiple heights.
- Easy to install into existing or new sockets, the Retro Post® is available as a surface or socket mount installation.







INLINE BOLLARD

DuraPost

- The Dura-Post® 360° Inline Bollard has a spring reinforced impact resistant polyurethane flexible joint which provides strength and durability, even for galvanised steel or aluminium posts.
- Multidirectional and impact absorbing, the inline bollard is easy to install and has vandal resistant fittings.
- Installation options include surface mount, ground socket or inground drivable anchor.

POLYFLEX™



- Manufactured from premium grade injection moulded polyurethane the Delnorth Poly-Flex™ range is UV stabilised and thermal resistant from -50° to +60°.
- Signficantly reducing replacement costs, Poly-Flex™ is strong and flexible, absorbs impact and returns to original position time after time making it perfect for high impact areas.
- Poly-Flex™ can be installed with ease and is available as a surface or socket mount.









RPS8049-R2-3AA	RPS8049 1000mm Round post fitted with Sign-Flex® 300mm x 400mm R2-3AA
RPS8156-R2-3A	RPS8156-1 1000mm Round post fitted with Sign-Flex® 450mm x 600mm R2-3A
RPS8050-R2-3A	RPS8052 600mm Flexi-Tuff® fitted with Sign-Flex® 450mm x 600mm R2-3A
RPS8050 -1-R23A-T	RPS8052-1 900MM Flexi-Tuff® fitted with Sign- Flex® 450mm x 600mm R2-3A-T (Tapered)
RPS8058	1550mm x 60mm Diameter round high grade rubber compound post suited to 50NB ground sockets
RPS8059	1000mm x 80mm x 40mm Rectangular high grade rubber compound sign post suited to ground sockets









FKL3900	Bollard flexible surface mount R2-3A keep left sign kit height 800mm
FBL5080	Bollard flexible white sign post height 800mm
FBL5100	Bollard flexible white sign post height 1000mm
FBL5227C	2.7m Inline aluminium bollard with 300mm galvanised base attached to red rubber, sits2.65m above red rubber base





POLY-FLEX™

PF11200	Socket mount poly-flex™ + poly post 1200mm
PF1121R2-209A	Socket mount keep left with sign-flex® R2- 209A fitted on 1200mm poly post
PF2S0900	Surface mount Poly-Flex™ + poly post 900mm
PF2S091R2-3A	Surface mount keep left with Sign-Flex® R2- 3A fitted on 900mm poly post
PF2S091R2-3AA	Surface mount keep left with Sign-Flex® R2- 3AA fitted on 900mm poly post